Ultimate Construction

4827 Pierceville Road Cottage Grove, WI 53527



WE BUILD BETTER, PERIOD! Your Home will be <u>comfortable</u> to live in, <u>safe</u> for your family, <u>durable</u> to last through the years, and <u>energy efficient</u> to save you money.

Congratulations, this Focus on Energy New Certified Home at <u>W8921 Ripley Road, Cambridge</u>, has **51.33% reduced cost of Ownership** over the New 2019 Wisconsin Building Code built home.

The Third Party building and energy consultant makes critical site visits during construction, and a final performance testing of the Home's components for **Quality Control and Assurances** that our building practices are in line with the highest Standards set for this climate by the Building Science Professionals.

HERS Index: 43 This is the National Standard for comparing home performance, like 'miles per gallon' is for a car. The Index is based on a comparison of the annual energy requirements for heating, cooling and hot water in the home being rated (with some standard operating conditions), to the annual energy requirements for the same home reconfigured to RESNET HERS *Reference Home*. The typical existing home score nationwide is 130, and the typical New Home score is 100. See: http://www.resnet.us/hers-index-large-scale

What about Air Tightness? The "blower door" air tightness test, shows our Homes to be among the tightest in Wisconsin. This not only provides <u>reduced operating costs</u>, but provides <u>draft free comfort</u> while <u>protecting the structure</u>. This added <u>durability</u> comes from a sealed thermal shell around your living space preventing mold, structural damage, and adding <u>lifetime value to your home</u>. Air tightness standards ask how much leakage is there on all 6 sides of the home, during a 20 mph wind. To compare homes we use this number:

0.05 cfm airflow @ 50 pa pressure difference / square feet of all the surface areas (all six sides of the box). The Focus on Energy New Homes Program Standard is 0.20 cfm @ 50 pa/sqft.

The average remodeled home in this area is 0.35 cfm @ 50 pa/sqft.

Can a house be too tight?

You have more control of Indoor Air because of the tight Home with adequate exhaust. Being capable of exhausting unwanted moisture and odors from the home is important, so each of your exhaust and intake devices has been tested. The indoor air quality is <u>under your control</u> and not so susceptible to outdoor fluctuations in temperature and humidity. To balance the humidity levels in your Home and/or get fresh air into your home, use the **Energy Recovery Ventilator.** This is an air to air exchanger that saves some of your exhaust heat and moisture, and has a tested exhaust flow of 84 cfm. This Model can be used in the humid months as well for fresh air intake. The Kitchen is vented to the exterior as well at 531 cfm, which is great for removing odors, moisture and gases from cooking.

Furnace / Air Conditioner / Water Heater

The Boiler is a **95%** efficient, cost effective model, that incorporates 'sealed combustion' technology to bring outside air in for combustion. And the **67%** high efficient side arm water heater, along with the boiler, will prevent combustion by-products from contaminating indoor air providing you with <u>greater safety</u>, and <u>energy efficiency</u>. You have a **13 SEER** Air Conditioner, which meets the Standards of the Industry.

Moisture and Radon reduction system. The sump pit is a sealed unit to prevent <u>unwanted Moisture and</u> Radon from entering your home.